

File No.: 11924-10US PM/jl

Montréal, Québec, Canada. March 1, 2000.

THE ASSISTANT COMMISSIONER FOR PATENTS Washington, D.C. 20231 USA



Sir:

Transmitted herewith for filing is the patent application of inventors Claude Barbeau and Ross Cochran.

For: "OUTER SHELL FABRIC FOR FIRE PROTECTIVE GARMENTS FOR FIREFIGHTERS AND FOR WORKERS EXPOSED TO RISK OF FLASH FIRE OR ELECTRIC ARC"

Your petitioner prays that letters patent may be granted for the invention set forth in the enclosed specification including: abstract, disclosure, claims, 3 figures of drawings (3 sheets) and also enclosed is an unsigned combined declaration on which all the details pertinent to the application will be found and verified statement claiming small entity status.

The Government fees, executed declaration and executed declaration of small entity will be filed as soon as we will receive the Notice of Missing Parts.

Attorney or Agents of the Applicant Paul Marcoux Registration No. 24,990

Swabey Ogilvy Renault

1981 McGill College Avenue

Suite 1600

Montréal, Québec, Canada H3A 2Y3

Enc.: Documents as Above

Post Card

		Claude Barbeau and Ross		
Serial or Patent No.:		Atty. Dkt. No.: _	11924-10US PM/jl	
Filed or Iss	ued:		•	
For: <u>"Ol</u>	UTER SHELL FABRI	IC FOR FIRE PROTECTIVE	GARMENTS FOR FIR	EFIGHTERS AND FOR
WORKERS	S EXPOSED TO RISK	OF FLASH FIRE OR ELECTR	IC ARC"	
	VERIFIED STATEM	MENT (DECLARATION) CLA 1.9(f) AND 1.27 (c)] - SMALL	AIMING SMALL ENTI	
I hereby dec	clare that I am			
() (x)	the owner of the smal	Il business concern identified be Il business concern empowered	low; to act on behalf of the con	cern identified below:
NA AD	ME OF CONCERN DRESS OF CONCERN	MARCANADA INC. 4200, boulevard St-Laurent	, 6° étage, Montréal (Québ	pec) CANADA H2W 2R2
reproduced in number of em number of em part-time or ten indirectly, one I hereby decidentified a GARMENT ARC" by in	37 CFR 1.9(d), for purpos aployees of the concern, inc ployees of the business concern property basis during each of concern controls or has the clare that rights under cabove with regard to the CS FOR FIREFIGHTER	small business concern qualifies as a less of paying reduced fees under section luding those of its affiliates, does not thern is the average over the previous fis of the pay periods of the fiscal year, and power to control the other, or a third pay contract or law have been converted invention, entitled "OUT AS AND FOR WORKERS EXPERTURED TO THE PART OF THE PART O	on 41(a) and (b) of Title 35, I exceed 500 persons. For purporal year of the concern of the persons are affiliates of each rty or parties controls or has the yed to and remain with the ER SHELL FABRIC FOOSED TO RISK OF FLA	Justed States Code, in that the coses of this statement, (1) the ersons employed on a full-time, the other when either, directly or a power to control both. The small business concern on FIRE PROTECTIVE
	the specification filed application serial no. patent no.	herewith; , filed	;	
If the rights he invention is lis inventor under 37 CFR 1.9(d) concern or org	eld by the above identified stated below* and no rights to a 37 CFR 1.9(c) if that perso or a nonprofit organization panization having rights to the	mall business concern are not exclusive the invention are held by any person, on made the invention, or by any concern a under 37 CFR 1.9(e). *NOTE: Sepa e invention averring to their status as sr	e, each individual, concern or or ther than the inventor who coul rn which would not qualify as rate verified statements are req	d not qualify as an independent a small business concern under
ADDRESS				
		() SMALL BUSINESS CONC		
status prior to	the duty to file, in this app paying, or at the time of pay ager appropriate. [37 CFR 1.	lication or patent, notification of any c ying, the earliest of the issue fee or any .28(b)]	hange in status resulting in los maintenance fee due after the	s of entitlement to small entity date on which status as a small
believed to be punishable by:	true, and further that these fine or imprisonment, or both	herein of my own knowledge are true e statements were made with the know h, under section 1001 of Title 18 of the ny patent issuing thereon, or any patent	vledge that willful false statem United States Code, and that su	ents and the like so made are
NAME OF	PERSON SIGNING	Page Cashran		
		N OWNER President	4.0	
ADDRESS	OF PERSON SIGNING	G 553, Grosvenor Avenue,	Westmount (Québec) CA	NADA H3Y 2S5

BACKGROUND OF THE INVENTION

(a) Field of the Invention

5

15

20

This invention relates to textile material for use as the outer shell fabric of a firefighter garment. More particularly, the invention is concerned with a lightweight outer shell fabric that is constructed of two different homogeneous yarn types in such a way as to increase resistance to mechanical and UV degradation while increasing thermal protective performance. In addition, the textile material can stretch, thereby increasing comfort and mobility.

10 (b) Description of Prior Art

All fabrics used in the manufacture of protective clothing for firefighters must satisfy minimum performance requirements for flame, heat and tear resistance as prescribed by the National Fire Protection Agency (NFPA).

A firefighter garment is normally made of a composite layer of materials including an outer shell fabric. All fabrics currently used for the outer shell fabric of firefighter garments are woven. The warps and wefts of the outer shell fabric usually comprise spun yarns that are either made up of homogeneous fibers or intimate blends of different fibers. The purpose of using intimate blends of fibers in yarns is to combine the individual strengths of each of the constituent fibers. However, since each fiber has its own weaknesses as well as strengths, the resulting intimate blend yarn must necessarily have some performance compromises as well.

Many of the fibers used in the yarns used in outer shell fabric fabrics of firefighter garments have drawbacks: difficulty in absorbing dye stuffs, poor color retention, UV degradation, fibrillation, poor abrasion resistance.

The fabric may be constructed as a plain, ripstop, twill, herringbone or other traditional weave construction; it will however,

20

25

30

appear as a continuous single sheet of yarns. And although there may be a face and a back surface to the weave construction, the face and back surfaces will consist of the identical yarns.

An alternative to spun yarns is multi-filamentary yarns. The latter have a much higher strength-to-weight and strength-to-denier ratios than the spun yarns of similar fibers. They are also more abrasion resistant and less water absorbing than spun yarns of the same fiber.

The principal disadvantages to multi-filamentary yarns are that the resulting fabrics are susceptible to yarn slippage.

The woven fabrics currently used as the outer shell fabric of fire protective garments, whether constituted of spun yarns, multifilamentary or both, fray and ravel after being torn, cut or punctured. Fraying and raveling not only degrade the appearance of the garment, they make repairs more difficult, and they may increase the risk of injury to the firefighter wearing the garment.

U.S. Pat. No. 5,299,602 discloses an outer shell fabric wherein the textile material comprises warps of alternating multi-filamentary aramid yarns and wefts of alternating spun aramid and multi-filamentary aramid yarns in a twill weave. The object of the invention disclosed in that Patent was to increase firefighter comfort and mobility without reducing mechanical resistance. However, this fabric is still more vulnerable to yarn and seam slippage than fabrics made with 100% spun yarns. Also as a consequence of the high percentage of multi-filamentary yarns, the fabric ravels and frays when cut or torn. Furthermore, the fabric has a preponderance of Kevlar® yarns on the face surface of the fabric and Kevlar® is more subject to mechanical and ultraviolet (UV) degradation than either spun or multi-filamentary Nomex®.

U.S. Pat. No. 5,527,597 discloses a woven firefighter fabric that incorporates a core-spun yarn (a Lycra[®] core protected by a

15

20

25

30

polybenzimidazole/aramid wrap) to impart a degree of elasticity to the fabric. Although the Patent claims that the fabric maintains its elasticity after five minutes at 500° F, the literature reveals that Lycra® is not thermally stable in firefighting environments: if stretched at temperatures above 370-390° F., Lycra® will lose its elasticity; above 415° F., Lycra® begins to char and lose its properties. Therefore, this stretchable fabric would suffer irreversible degradation in a firefighting environment.

It is therefore an object of the present invention to provide a stretchable fabric wherein the yarns such as aramid yarns would maintain their integrity at temperatures in excess of 600° F.

It is another object of the present invention to provide a textile material for the outer shell fabric of a firefighter garment that is lightweight yet has increased abrasion, tear, and UV resistance.

It is another object of the present invention to provide a textile material for the outer shell fabric of a firefighter garment that has a higher thermal protective performance rating than conventional fabrics of the same weight and fiber type.

It is another object of the present invention to achieve elasticity through the inherent stretchiness of a warp knit construction and not through the introduction of thermally unstable elastomers.

It is a further object of the present invention to provide a warp knit textile material that can be used to produce a firefighter outer shell fabric that is more resistant to fraying and raveling than the currently used woven fabrics.

SUMMARY OF THE INVENTION

In accordance with the present invention, there is provided a textile material to constitute an outer shell fabric for fire-resistive garments, the textile material being a textile arrangement of at least first

15

20

25

30

and second inherently fire-resistant yarns, the first and second yarns being different from one another, the textile arrangement including interlacing means joining the first and second yarns.

Preferably, the textile arrangement is a warp knit or a double 5 weave.

In accordance with a preferred embodiment, the first yarns are of first fiber type, and the second yarns are of a second fiber type which is different from the first fiber type.

The first yarns may be multi-filamentary yarns of the first fiber type and the second yarns may be spun yarns or multi-filamentary yarns of the second fiber type.

In accordance with another embodiment, the first yarns are exposed on a major part of a face of the outer shell fabric, and the second yarns are exposed on a major part of a back surface of the outer shell fabric. For example, the second yarns are exposed on less than about 15% of the face of the outer shell fabric, the first yarns are exposed on more than about 85% of the face of the outer shell fabric, and the second yarns are exposed on more than about 75% of the back surface of the outer shell fabric.

In accordance with yet another embodiment, the multifilamentary yarns of the one fiber type are made up of one or more fibers selected from the group consisting of meta-aramid, para-aramid, polyimide, polybenzimidazole, polynosic rayon, polyimide-amide, polybenzoxazole, methacrylic and melamine fibers.

In accordance with another embodiment, the second yarns are spun yarns which are different from the first yarns and are made up of a fiber or a blend of fibers different from the multi-filamentary yarns.

In accordance with yet another embodiment, the second yarns are multi-filamentary yarns which are different from the first yarns and are made up of a fiber or a blend of fibers different from the multi-

15

20

25

30

filamentary yarns of the first yarns. Preferably, the first yarn type consists of Nomex[®] and the second yarn type consists of Kevlar[®].

The textile material according to the invention may comprise at least one additional and different yarn.

When the textile material according to the invention is a warp knit it may be produced by using two bars of different warp yarns on a Raschel machine.

The interlacing means may comprise warp yarns of the first type shared by both upper and bottom surfaces, or may comprise weft yarns of the first fiber type and shared by both upper and bottom surfaces, or may comprise warp and weft yarns of the first fiber type and shared by both upper and bottom surfaces. The interlacing means may comprise knitted loops of yarns.

When the textile arrangement is a double weave, the interlacing means may comprise an interlacing yarn which is common to both the upper and the bottom surfaces.

In accordance with another preferred embodiment, the first yarns are more dyeable, more resistant to UV degradation, and more resistant to fibrillation than the second yarns.

In accordance with a preferred embodiment of the invention, multi-filamentary yarns comprising fibers such as meta-aramid constitute greater than 85% of the yarns on the face surface of the textile material. Conversely, either spun or multi-filamentary yarns comprising fibers such as para-aramid form more than 75% of the yarns on the back surface of the textile material.

In one embodiment of the invention, a double-weave woven fabric, warp yarns in the face fabric will periodically drop down to become warp yarns in the back fabric. In this manner, the face and back fabrics are interlaced by having common warp yarns. In another embodiment of a double-weave fabric, the interlacing yarns may be weft

10

20

(fill yarns). It would also be possible to provide interlacing common yarns in both the warp and the weft directions.

In another embodiment of the present invention, a warp-knit fabric, there are no weft yarns, only warp yarns. The warp yarns form continuously interlacing loops to make a length of fabric. In the warp-knit embodiment of the present invention multi-filamentary meta-aramid yarns are placed on one bar while spun or multi-filamentary para-aramid yarns are placed on a second bar. The loops of yarn from one bar are interlaced with loops of yarn from the other bar in a manner such that there is a preponderance of multi-filamentary meta-aramid yarn loops on the face surface and a preponderance of para-aramid spun or multi-filamentary yarn loops on the back surface.

BRIEF DESCRIPTION OF DRAWINGS

The invention is illustrated, but not restricted, by the annexed drawings of preferred embodiments in which

FIGURE 1 is an illustration in plan view on an enlarged scale of a conventional woven fabric of the prior art;

FIGURE 2 is an illustration in edge view on an enlarged scale of a double-weave fabric according to the invention for the outer shell fabric of a firefighter garment; and

FIGURE 3 is an illustration in plan view on an enlarged scale of the back surface of a warp knit fabric according to the invention.

25 DESCRIPTION OF PREFERRED EMBODIMENTS

Referring to FIGURE 1, it will be seen that in a conventional woven fabric 10, the warp yarns 2 and the west yarns 1 are of the same type of yarns, for example spun yarns and are of the same fiber composition, such as aramid, or an intimate blend of the same fibers.

10

15

20

25

Turning now to FIGURE 2 which illustrates a double weave, the upper face 3 of the double weave consists of a warp of yarns 4 and a weft of yarns 5, here both Nomex[®], wherein Nomex[®]yarns 4 are predominantly exposed on upper surface 3. Bottom surface 6, on the other hand is a warp and weft weave of yarns 7 and 8, here both Kevlar[®], wherein Kevlar[®] is predominantly exposed on bottom surface 6. The two weaves constituting upper surface 3 and bottom surface 6 are interlaced as shown by means of intermittent warp yarns 4 consisting of Nomex[®].

Referring now to FIGURE 3, the warp knit which is illustrated is a pillar stitch and cord stitch construction as commonly called in warp knit terminology. Warp knit yarns 11 forming the pillar stitch are multifilamentary Nomex[®] which are exposed on a major part of the face surface 15 of fabric 12, while warp knit yarns 13 are either spun or multi-filamentary Kevlar[®] which are exposed on a major part of the back surface 14 of fabric 12.

It has been found that the textile material according to the invention whether of warp knit or double weave construction has more interstices than current woven outer shell fabrics. These interstices trap air which provides additional thermal insulation as measured by the Thermal Protective Performance (TPP) test of NFPA.

Furthermore, because the yarns used on the face (upper) and back (bottom) surfaces of the textile material are of different fiber types, the two surfaces react differently when exposed to heat fluxes in excess of 1.0 cal/cm²/sec. The difference in reactions of the two surfaces causes the fabric to distort itself thereby creating an additional layer of insulating air.

It is understood that modifications are possible within the scope and spirit of the present invention as defined in the appended claims.

We claim:

- 1. A textile material to constitute an outer shell fabric for fireresistive garments, said textile material being a textile arrangement of at
 least first and second inherently fire-resistant yarns, said first and second
 yarns being different from one another, said textile arrangement
 including interlacing means joining said first and second yarns.
- 2. Textile material according to claim 1, wherein said textile arrangement is a warp knit.
 - 3. Textile material according to claim 2, wherein said first yarns are of first fiber type, and said second yarns are of a second fiber type or blend of fibers which is different from said first fiber type.
- 4. Textile material according to claim 3, wherein said first yarns are multi-filamentary yarns of said one fiber type.
 - 5. Textile material according to claim 4, wherein said second yarns are spun yarns.
 - 6. Textile material according to claim 4, wherein said second yarns are multi-filamentary yarns of said second fiber type.
- 7. Textile material according to claim 1, wherein said first yarns are exposed on a major part of a face of said outer shell fabric.
 - 8. Textile material according to claim 7, wherein said second yarns are exposed on a major part of a back surface of said outer shell fabric.
- 9. Textile material according to claim 7, wherein said second yarns are exposed on less than about 15% of said face of said outer shell fabric and said first yarns are exposed on more than about 85% of said face of said outer shell fabric.
 - 10. Textile material according to claim 9, wherein said second yarns are exposed on more than about 75% of the back surface of said outer shell fabric.

- 11. Textile material according to claim 4, wherein said multifilamentary yarns of said first fiber type are made up of one or more fibers selected from the group consisting of meta-aramid, para-aramid, polyimide, polybenzimidazole, polynosic rayon, polyimide-amide, polybenzoxazole, methacrylic and melamine fibers.
- 12. Textile material according to claim 11 wherein said second yarns are spun yarns which are different from said first yarns and are made up of a fiber or blend of fibers selected from the group consisting of meta-aramid, para-aramid, polyimide, polybenzimidazole, polynosic rayon, polyimide-amide, polybenzoxazole, methacrylic and melamine fibers.
- 13. Textile material according to claim 1, wherein said second yarns are multi-filamentary yarns which are different from said first yarns and are made up of a fiber or blend of fibers selected from the group consisting of meta-aramid, para-aramid, polyimide, polybenzimidazole,
- polynosic rayon, polyimide-amide, polybenzoxazole, methacrylic and melamine fibers.
 - 14. Textile material according to claim 8, wherein said first yarn type consists of Nomex[®] yarn and said second yarn type consists of Kevlar[®] yarn.
- 20 15. Textile material according to claim 1, which comprises at least one additional yarn type.
 - 16. Textile material according to claim 2, wherein said warp knit is produced by using two bars of different warp yarns on a Raschel machine.
- 25 17. Textile material according to claim 1, wherein said textile arrangement is a double weave.
 - 18. Textile material according to claim 17, wherein said interlacing means comprise warp yarns of the first fiber type and shared by both upper and bottom surfaces.

25

- 19. Textile material according to claim 17, wherein said interlacing means comprise weft yarns of the first fiber type and shared by upper and bottom surfaces.
- 20. Textile material according to claim 17, wherein said interlacing means comprise warp and weft yarns of the first fiber type and shared by both upper and bottom surfaces.
 - 21. Textile material according to claim 17, wherein said interlacing means comprise a yarn which is common to both upper and bottom surfaces.
- 10 22. Textile material according to claim 17, wherein said first yarns are of one fiber type, and said second yarns are of a second fiber type which is different from said one fiber type.
 - 23. Textile material according to claim 22, wherein said first yarn is a multifilamentary yarn of said one fiber type.
- 15 24. Textile material according to claim 22, wherein said second yarn is a spun yarn of said second fiber type.
 - 25. Textile material according to claim 22, wherein said second yarn is a multi-filamentary yarn of said second fiber type.
- 26. Textile material according to claim 17, wherein said first yarns are exposed on a major part of a face of said outer shell fabric and said second yarn are exposed on a major part of a back surface of said outer shell fabric.
 - 27. Textile material according to claim 26, wherein said interlacing means comprise an interlacing yarn which is common to both said face and said base surface.
 - 28. Textile material according to claim 1, wherein said first yarns are more dyeable, more resistant to UV degradation, and more resistant to fibrillation than said second yarns.
- 29. Textile material according to claim 23, wherein said multi-30 filamentary yarns of said one fiber type is made up of on or more fibers

selected from the group consisting of meta-aramid, para-aramid, polyimide, polybenzimidazole, polynosic rayon, polyimide-amide, polybenzoxazole, methacrylic and melamine fibers.

- 30. Textile material according to claim 24, wherein said spun yarn is made up of a fiber or blend of fibers selected from the group consisting of meta-aramid, para-aramid, polyimide, polybenzimidazole, polynosic rayon, polyimide-amide, polybenzoxazole, methacrylic and melamine fibers.
- 31. Textile material according to claim 24, wherein said multifilamentary yarns is different from said first yarn and made up of a fiber or blend of fibers selected from the group consisting of meta-aramid, para-aramid, polyimide, polybenzimidazole, polynosic rayon, polyimide-amide, polybenzoxazole, methacrylic and melamine fibers.

10


15

20


Outer Shell Fabric for Fire Protective Garments for Firefighters and for Workers Exposed to Risk of Flash Fire or Electric Arc.

ABSTRACT OF THE DISCLOSURE


The outer shell fabric according to the invention is made of a textile material which is a double-weave woven fabric or a warp-knit knitted fabric constructed in such a manner that preferably a majority of one yarn type is placed on the face of the fabric and the majority of a different yarn type is placed on the back surface. One of the yarns may consist of multi-filamentary meta-aramid fiber (e.g. Nomex), the other of either a multi-filamentary or a spun (staple) para-aramid fiber (e.g. Kevlar). The textile material can be visualized as two separate fabrics being interlaced together by the sharing of yarns between them. When used as part of a firefighter or work garment for protection against heat and flame, the outer shell fabric has superior tear resistance, abrasion resistance, UV resistance, and thermal protective performance when compared to other outer shell fabrics used for the same application. In addition, the textile material is more elastic than traditional woven fabrics of the same yarns, and when used in conjunction with a firefighter garment, increases comfort and mobility.



F16. 1



F16.2



Application Serial No.

Combined Declaration for Patent Application and Power of Attorney

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe that I am the original, first and sole inventor (if only one name listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled <u>"OUTER SHELL FABRIC FOR FIRE PROTECTIVE GARMENTS FOR FIREFIGHTERS AND FOR WORKERS EXPOSED TO</u> RISK OF FLASH FIRE OR ELECTRIC ARC", the specification of which

X	is attached hereto.			
[]	was filed on	as A	Application No.	
	and (if applicable) was amended	on		
	e that I have reviewed and unders any amendment referred to above		bove-identified specification, in	cluding the claims, as
	e the duty to disclose information of Federal Regulations, § 1.56		e examination of this application	on in accordance with
inventor's ce	n foreign priority benefits under intificate listed below and have a date before that of the application	so identified below any f	oreign application for patent or	
		Prior Foreign Applicat	cion(s)	
Number	Co	untry	Day/Month/Year Filed	Priority Claimed
			- I i l Company	-/-\ listed balancand
insofar as the the manner material info	m the benefit under Title 35, Un e subject matter of each of the cl provided by the first paragraph rmation as defined in Title 37, Co lication and the national or PCT ir	aims of this application is of Title 35, United State de of Federal Regulations,	not disclosed in the prior Unite s code, § 112, I acknowledge § 1.56(a) which occurred betv	d States application in the duty to disclose

I hereby appoint the following attorneys, with full power of substitution, association, and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith. ROBERT MITCHELL, Registration No. 25,007, GUY HOULE, Registration No. 24, 971, PAUL MARCOUX, Registration No. 24,990, KEVIN P. MURPHY, Registration No. 26,674; ROBERT CARRIER, Registration No. 30,726; and address all correspondence to:

Status (Patented, Pending, Abandoned)

Day/Month/Year Filed

SWABEY OGILVY RENAULT 1981 McGill Avenue **Suite 1600** Montréal, Québec, Canada H3A 2Y3 Telephone No. (514) 845-7126

I hereby further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued

thereon.							
Full name of sole or first inventor Claude Barbeau	Inventor's signature			Date			
Residence 1875, rue de la Duchesse, St-Bruno (Québec) CANADA J3V 3M1	Citizenship	CANADI	AN				
Post Office address 1875, rue de la Duchesse, St-Bruno (Québec) CANADA J3V 3M1							
Full name of second inventor Ross Cochran	Inventor's signature			Date			
Residence 553, Grosvenor Avenue, Westmount (Québec) CANADA H3Y 2S5		Citizenship	CANADIAN				
Post Office address 553, Grosvenor Avenue, Westmount (Québec) CANADA H3Y 2S5							